













*Fabricated Fittings (non-SABS)

REDI LARGE BORE FITTINGS

<p>Access Stopped</p> <p>*UAP621651603 – 160mm</p> 	<p>45° Plain Bend Double Socketed</p> <p>*UB61S23165 – 160mm</p> 	<p>87.5° Plain Bend Double Socketed</p> <p>*UB62S24165 – 160mm *UB8224215 – 200mm</p> 	<p>Double Socket</p> <p>*UE60163165 – 160mm *UE80163205 – 200mm</p> 
<p>Adaptor PVC to EW Spigot/Socket</p> <p>*UE6162165 – 160mm</p> 	<p>Kimberley Socket</p> <p>*UK6061165 – 160mm</p> 	<p>45° Plain Junction</p> <p>*UY6144165 – 160mm</p> 	<p>87.5° Plain Square Junction</p> <p>*UY6245165 – 160mm</p> 
<p>45° Plain Reducing Junction</p> <p>*UY84312151 – 200mm x 160mm</p> 	<p>Non-Return Valves</p> <p>*1555551 – 110mm *1551691 – 160mm</p> 	<p>Taper Pipe</p> <p>*UT600 160mm x 110mm</p> 	

REDI



Marley Flood Valve/Non-Return Sewer Valve are moulded with rubber / spigot rings for a secure and reliable seal. Designed for non-pressure applications in underground drainage, featuring a lockable butterfly flap for ease of maintenance.

REDI fittings are manufactured according to EN1452-2 standards, complying with the requirements as set out by the European Standard Institute.

The fittings are totally compatible with SABS 791 (solid wall) and SABS 1601 (foam wall PVC pipes)

REDI provides easy-to-install, secure and reliable solutions aimed at building long-lasting networks.